



## Gravity Applications

Excellent for handling odd shaped boxes, bags and low grade cartons

- 220 kg capacity per linear metre (level)
- 762 to 1080 mm adjustable conveyor height
- 450, 600 and 750 mm conveyor widths
- Available in any length to fit your applications

## Performance Options




### Package Stop

Stops cartons at the end of the conveyor and can be dropped down when not needed.




### Side Rails

Prevents cartons from running off the conveyor in accumulating applications.



### Roller Connector

Easily connects two or more conveyors to span greater distances.



### Axle Centres

In addition to the standard axle centre of 127mm options of 76mm and 102mm are available on request to handle smaller packages.



### 150mm x 50mm Swivel Castors

For easier rolling over uneven surfaces. Adds 23mm to conveyor height.



### Perpendicular Legs

Keeps legs vertical in both the expanded and compacted positions for easier mobility and added strength.

## Features

- Self Tracking – Cartons follow the twists and turns of the conveyor path without using engineered curves.
- Adjustable Height – Adjustable locking bolts to raise or lower the conveyor bed height.
- Square Tubing Legs – heavy duty square tubing legs offer longer service life and stability.
- 38mm Side Plates – Aluminium alloy construction features a ribbed design for added durability. Assembled with bolts and lock nuts.
- Castors with brakes – 127mm x 38mm swivel castors roll easily. Castor brakes lock both wheel and swivel simultaneously while the conveyor is in use.

## Specifications

	Model Number	Standard Lengths Compacted To Expanded	Leg Sets Per Unit	Approx Shipping weight
<b>450mm Widths</b>	BFR - 18-12	3.66m - 1.25m	4	102 kg
	BFR - 18-16	4.88m - 1.65m	5	132 kg
	BFR - 18-20	6.10m - 2.04m	6	163 kg
	BFR - 18-24	7.32m - 2.44m	7	193 kg
<b>600mm Widths</b>	BFR - 24-12	1.20m - 3.70m	4	109 kg
	BFR - 24-16	1.60m - 4.90m	5	138 kg
	BFR - 24-20	2.00m - 6.10m	6	170 kg
	BFR - 24-24	2.40m - 7.30m	7	200 kg
<b>750mm Widths</b>	BFR - 30-12	1.20m - 3.70m	4	116 kg
	BFR - 30-16	1.60m - 4.90m	5	145 kg
	BFR - 30-20	2.00m - 6.10m	6	177 kg
	BFR - 30-24	2.40m - 7.30m	7	206 kg

All Best Conveyors products can be modified to suit specific design requirements. Please contact our sales representatives for details on sizes or options that are not listed.